WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau




INTERNATIONAL APPLICATION PUBLIS	IDER THE PATENT COOPERATION TREATY (PCT)			
(51) International Patent Classification 6:	A1	(11) International Publication Number: WO 97/40480		
G08B 21/00, H04M 11/04, G07B 17/00		(43) International Publication Date: 30 October 1997 (30.10.97)		
(21) International Application Number: PCT/US (22) International Filing Date: 23 April 1997 (2)		DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT,		
(30) Priority Data: 60/015,526 60/043,445 23 April 1996 (23.04.96) 9 April 1997 (09.04.97)	i i			
(71) Applicant (for all designated States except US): HASLER MAILING SYSTEMS, INC. [US/US]; 1 Parkway, Shelton, CT 06484 (US).				
(72) Inventor; and (75) Inventor/Applicant (for US only): BROOKNER, [US/US]; 11 Surrey Drive, Norwalk, CT 06851 (U.	Georg			
(74) Agent: FERENCE, Stanley, D., III; Oppedahl & Larso 309, 1992 Commerce Street, Yorktown Heights, NY 4412 (US).				
	,			

(54) Title: SYSTEM FOR PROVIDING EARLY WARNING PREEMPTIVE POSTAL EQUIPMENT REPLACEMENT

(57) Abstract

An improved system for providing early warning preemptive postal equipment replacement. Selected performance parameters of the postal equipment are monitored and compared against predetermined operational boundaries. The system is capable of prodiving for variability in the performance parameters, wherein these parameters may be permitted to vary over time and usage of the equipment. The monitoring gives an indication of the overall system performance. If the system performance goes outside of operational boundaries, or changes significantly over time, replacement of the equipment can then be scheduled with minimal inconvenience to the customer.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Słovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	ΙΤ	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE.	Konya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	2W	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
		KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucis	RU	Russian Federation		
CZ	Czech Republic	Ш	Liechtenstein	SD	Sudan		
DE	Germany		Sri Lanka	SE	Sweden		
DK	Denmark	LK	Liberia	SG	Singapore		
EE	Estonia	LR	Liberia	30	Singapore		

SYSTEM FOR PROVIDING EARLY WARNING PREEMPTIVE POSTAL EQUIPMENT REPLACEMENT

RELATED APPLICATIONS

This application claims priority from pending
U.S. Provisional Application Serial No. 60/015,526, filed
on April 23, 1996, and a pending U.S. Provisional
Application entitled "Proof of Postage Digital Franking
System," Attorney Docket No. ASCOP043US, filed on April
9, 1997, for which a Serial No. has yet to be assigned,
both of which are hereby incorporated by reference.

TECHNICAL FIELD

The present invention relates generally to predicting when a device is likely to fail, and in particular to such prediction in postal equipment, such as postage meters, also called franking machines.

BACKGROUND ART

In countries such as the United States, the postal authority does not permit a customer to actually own a postage meter. Rather, the postal customer rents the postage meter from a manufacturer approved by the postal authority, such as the assignee of the present application. This meter is then used at the postal customer's facility.

In the United States, the postal customer

traditionally adds postage to the meter in two ways. The
first is to physically take the meter to the postal
authority where postage is purchased and added to the
meter. The second is to remotely add postage over the
telephone line with a modem wherein the added postage is

deducted from an account maintained with the meter's manufacturer.

While postal equipment in general, and postage meters in particular, are designed to be extremely reliable, on occasion a customer's meter has been known to fail. Generally speaking, there are two types of failures, catastrophic and non-catastrophic. The non-catastrophic is by far the most common of the two, and occurs when some component of the postage meter ceases to operate, such as the display, a mechanical linkage, etc. A catastrophic failure occurs when some or all of the information stored in nonvolatile memory is not recoverable, as discussed below.

The consequence of a non-catastrophic meter 15 failure is primarily one of customer inconvenience. When such a failure occurs, the customer no longer has use of the equipment and must call for technical support. field repair or replacement must then be scheduled, which further lengthens the "down time" of the equipment for the customer. In the case of a metering device, the 20 failed device needs to be removed from service, the postal authority notified, and a replacement unit logged with the postal authority, and then finally provided to Depending on what component failed, the customer. certain information contained in the failed meter may be 25 transferred to the replacement meter by the service technician.

In an electronic postage meter the amount of postage available for printing (or printed) is stored in a nonvolatile memory. It may be desirable to store the accounting data redundantly, as set forth in PCT pub. no. WO 89-11134, which is incorporated herein by reference. In addition, it may be desirable that the redundant

30

memories be of differing technologies, as set forth in the aforementioned PCT publication. Finally, it is extremely desirable to protect the memory from harm due to processor malfunction, as set forth in US pat. no. 5,276,844, in EP pub. no. 527010, or in EP pub. no. 737944, each of which is incorporated herein by reference.

The user of an electronic postage meter should not be able to affect the stored postage data in any way 10 other than reducing it (by printing postage) or increasing it (by authorized resetting activities). single stored location must necessarily be relied upon by all parties (the customer, the postal authority, and the provider of the meter) as the sole determinant of the 15 value of the amount of postage available for printing. In electronic postage meters, the single stored location is the secure physical housing of the meter itself. Within the secure housing, one or more items of data in one or more nonvolatile memories serve to determine the 20 amount of postage available for printing.

While a catastrophic failure is rare, the consequences of a catastrophic failure are far more severe, namely loss by the user of postage value for which the postal authority has already been paid.

Furthermore, it is possible that in a catastrophic failure no information contained in the failed meter may be transferred to the replacement meter by the service technician. Thus, there is also the loss of historical data which may be of value to the customer.

30 DISCLOSURE OF INVENTION

In accordance with the present invention, there is provided a greatly improved system providing early

warning preemptive postal equipment replacement.

According to the invention, it is provided that selected performance parameters of the postal equipment are monitored and compared against predetermined operational boundaries. The monitoring gives an indication of the overall system performance. If the system performance goes outside of operational boundaries, or changes significantly, replacement can be scheduled with minimal inconvenience to the customer. Data from the old meter can then be orderly transferred to the replacement meter.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of the system of the present invention used with a postage meter.

Fig. 2 is a flow chart of the method for providing early warning according to the invention.

Fig. 3 is a flow chart of the method for providing early warning according to another embodiment of the invention.

MODES FOR CARRYING OUT THE INVENTION

Referring to Fig. 1, a system in accordance with the invention is shown generally at 10, and includes a line or communications link 12 for communicating with a Data Center (not shown) used in remote resetting of postage meters having a communication device such as a telephone 14 therein, a Central Processing Unit (CPU) 16, non-volatile memory 18, read only memory (ROM) 20, random access memory (RAM) 22, input means 24, display means 26, and print means 28. The CPU 16 is connected to a Data Center through communications link or line 12. Processor 16, read only memory 18, random access memory 22, input

5

means 24, display means 26, and print means are coupled with each other by system bus 30.

Referring now to Fig. 2, a flow chart is shown wherein the deviation of system parameters is determined in connection with remote resetting of the meter. Generally, the meter communicates with a Data Center maintained by the meter manufacturer, which in turn communicates with a bank or other holder of funds. If funds sufficient to cover the requested amount of postage are on deposit, then that amount of postage is added to the meter. Systems for the resetting of meters remotely through the use of Data Center are known in the art.

Telemeter setting (TMS) may be carried out as set forth in EPO pub. no. EP 442761, or as set forth in PCT pub. no. WO 86-05611, each of which is incorporated herein by reference.

Once communication has been established between processor 16 and the Data Center, the processor 16 is instructed to monitor certain preselected system parameters, such as motor acceleration and speed, solenoid actuation time, sensor switching time, internal diagnostic history, spare CPU band pass, non-volatile memory useable address locations remaining, display element integrity, value setting time, cycles printed, etc. The motor and solenoid are typically contained in print means 28.

Processor 16 then algorithmically represents the data on the preselected system parameters through a "Metering Health Code" (MHC), which periodically (for the purposes of determining the time periods between MHC generations) summarizes the performance level of the system and remains resident in the metering system, for example in non volatile memory 18. The present invention

5

10

15

20

25

includes the capability of providing for variability in the performance measuring parameters wherein said performance monitoring parameters may be made to vary over time (e.g., aging) and usage such that it is possible and desirable to accept the performance of an older(er) product/device and yet not accept the same performance when attributed to a new product/device. "Meter Health Code" can be stored in the postage meter and compared against predetermined parameters by the Data Center, or as preferred employment, the Data Center would also maintain a history of the postage meter's health codes and have the ability to evaluate each postage meter against its own health code degradation. In this manner, a postage meter which is degrading very slowly can be left in service longer than a postage meter that shows a more rapid degradation pattern. Another preferred embodiment of this invention is to execute a benchmark evaluation of the postage meter at the time of manufacture, said benchmark would reside within the postage meter memory as well as within the Data Center's history file applied to that specific postage meter.

The "Metering Health Code" is then communicated to the Data Center where it is evaluated to determine if the meter is a candidate for replacement. Such evaluation need not occur during the communication with the meter, but may occur at another time. Alternatively, such evaluation may occur within the meter itself, with the result of the evaluation being transmitted to the Data Center.

Rather than generate the "Meter Health Code" in the meter, and communicate the result to the Data Center for evaluation, alternatively the parameters underlying the "Metering Health Code" may be communicated to the

15

20

Data Center and the "Metering Health Code" will be determined and evaluated at the Data Center.

Evaluation of the "Meter Health Code" assures
the system is performing within acceptable boundaries at
the time the "Meter Health Code" is determined.
Furthermore, monitoring changes system performance over
time is beneficial. Even if overall system performance
at a given point in time is within acceptable boundaries,
a change in the "Metering Health Code" would signal a
need to monitor the system closely or to perform
preventative maintenance, or in the case of a meter,
replace it prior to a failure resulting in "down time"
for the customer.

With an early warning of impending failure, a 15 replacement can be scheduled with no inconvenience to the customer. The physical exchange could be made during a period of non-use by the customer. Furthermore, the customer's accounting and historical system information maintained within the customer's meter can be 20 reconfigured into the new meter via modem at the time the new meter is "logged" into the Data Center. For example, said customer-use specific accounting and historical data (from the customer's existing meter) would be uploaded to the Data Center prior to meter replacement. When the new meter "logs" on with the Data Center, said customer data 25 is downloaded into the replacement meter. The customer is now able to continue system usage without any of his customer-specific data having been changed.

Referring now to Fig. 3, a flow chart is shown
30 wherein the generation of "Meter Health Code" occurs in response to an input from other than the Data Center during funds recharging. In this embodiment of the invention, the process of the present invention is

commenced in response to the appropriate command given during a routine inspection via the modem or keyboard/display by entering a code which extracts and transmits the quantitative performance data to the Data Center or displays/prints the quantitative performance data to the user.

While there have been described what are believed to be the preferred embodiments of the invention, those skilled in the art will recognize that other and further modifications may be made thereto without departing from the invention and it is intended to claim all such changes and modifications as fully within the scope of the invention.

I CLAIM:

 A system for providing early warning preemptive postal equipment replacement, comprising:

means for communicating with a Data 5 Center;

processor means for monitoring selected system parameters responsive to a communication from said Data Center;

means for summarizing said selected system

10 parameters to reflect the performance level of the system;

means for communicating said summarized performance level of the system to said Data Center.

- The system as described in Claim 1,
 wherein said means for communicating with a Data Center is a modem.
 - 3. The system as described in Claim 1, wherein said means for communicating with a Data Center is a global communications network.
- 4. A system for providing early warning preemptive postal equipment replacement, comprising:

means for communicating with a Data
Center;

processor means for monitoring selected

25 system parameters responsive to a communication from said

Data Center;

means for summarizing said selected system parameters to reflect the performance level of the system;

means for communicating said summarized performance level of the system to said Data Center;

means for evaluating said summarized performance level of the system to determine if replacement of the postal equipment is warranted.

- 5. The system as described in Claim 4,
 wherein said means for communicating with a Data Center is a modem.
 - 6. The system as described in Claim 4, wherein said means for communicating with a Data Center is a global communications network.
- 7. A system for providing early warning preemptive postal equipment replacement, comprising:

processor means for monitoring selected
system parameters;

means for summarizing said selected system 20 parameters to reflect the performance level of the system;

means for communicating said summarized performance level of the system to a user of the system.

8. The system as described in Claim 7,
wherein said means for communicating said summarized
performance level of the system to a user of the system

is a liquid crystal display or other technology capable of visually presenting computer derived information.

- 9. A system for providing early warning preemptive postal equipment replacement, comprising:
- 5 processor means for monitoring selected system parameters on a periodic basis;

means for summarizing said selected system parameters to reflect the performance level of the system;

- memory means for storing said summarized performance level of the system.
 - 10. A method for providing early warning preemptive postal equipment replacement, comprising:

communicating with a Data Center;

monitoring selected system parameters responsive to a communication from said Data Center;

summarizing said selected system parameters to reflect the performance level of the system;

evaluating said summarized performance level of the system to determine if replacement of the postal equipment is warranted.

25 11. A method for providing early warning preemptive postal equipment replacement, comprising:

monitoring selected system parameters;

summarizing said selected system parameters to reflect the performance level of the system;

- 5 evaluating said summarized performance level of the system to determine if replacement of the postal equipment is warranted.
 - 12. A method for providing early warning preemptive postal equipment replacement, comprising:

summarizing said selected system parameters to reflect the performance level of the system;

- communicating said summarized performance level of the system to a user of the system.
 - 13. A method for providing early warning preemptive postal equipment replacement, comprising:


monitoring selected system parameters;

summarizing said selected system


20 parameters to reflect the performance level of the system;

storing said summarized performance level of the system.

14. The method as described in Claim 13,25 wherein said monitoring is performed periodically.



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/06837

p-				
A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :G08B 21/00; H04M 11/04; G07B 17/00				
US CL	:364/551.01; 340/514, 679, 825.55; 364/464.2; 379/49, 90			
According	to International Patent Classification (IPC) or to both national classification	assification and IPC		
	LDS SEARCHED		· · · · · · · · · · · · · · · · · · ·	
Minimum d	ocumentation searched (classification system followed by classif	ication symbols)		
U.S. :	364/551.01; 340/514, 679, 825.55; 364/464.2; 379/49, 90			
1	tion searched other than minimum documentation to the extent that	such documents are included	in the fields searched	
NONE.				
Pleetronic of NONE.	lata base consulted during the international search (name of data	base and, where practicable	, scarch terms used)	
C. DOC	CUMENTS CONSIDERED TO BE RELEVANT			
Category*	Citation of document, with indication, where appropriate, or	of the relevant passages	Relevant to claim No.	
A	A, US, 4,234,926 (WALLACE et al) 18 No abstract.	ovember 1980, se	1, 2, 4, 5, 7 & 9-14	
A	A, US, 5,008,827 (SANSONE et al) 16 April 1991, see 1, 2, 4, 5, 7 & abstract. 9-14			
Α	A, US, 5,043,908 (MANDULEY et al) 27 August 1991, see 1, 2, 4, 9-14			
A	A, US, 5,063,857 (KISSEL, JR.) 12 November 1991, see 1, 2, 4, 5, 7 & abstract. 9-14			
A	A, US, 5,276,844 (AEBI et al) 04 January 1994, see 1, 2, 4, 5, 7 & abstract. 9-14			
		·		
Furth	er documents are listed in the continuation of Box C.	See patent family annex.		
 Special categories of cited documents: "I" later document published after the international filing date or priority 				
"A" document defining the general state of the art which is not considered to be part of particular relevance				
	tion downward authliched an an after the intermedianal Cities date "X" de	ocument of particular relevance; the	claimed invention cannot be	
"L" document which may throw doubts on priority claim(s) or which is cited to establish the rublication date of another citetion or other				
special reason (as specified) "O" document of particular relevance; the claimed invention cannot be considered to inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art				
P document published prior to the international filing date but later than the priority date claimed document member of the same patent family				
Date of the actual completion of the international search Date of mailing of the international search report				
26 JUNE 1997 3 1 JUL 1997				
	Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Authorized officer			
Box PCT	, D.C. 20231 EDWA	R. COSIMANO,		
Facsimile No. (703) 305-3230 Telephone No. (703) 308-3900				
Form PCT/ISA/210 (second sheet)(July 1992)#				

INTERNATIONAL SEARCH REPORT

International application No. PCT/US97/06837

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)
This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:
1. Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:
2. Claims Nos.: 3, 6 & 8 because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically: Claims 3, 6 & 8 are directed to subject matter which is not supported by the disclosure.
3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).
Box II Observations where unity of invention is tacking (Continuation of item 2 of first sheet)
This International Searching Authority found multiple inventions in this international application, as follows:
RECEIVED AUG 28 2001 OIPE/JCWS
1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
Remark on Protest The additional search fees were accompanied by the applicant's protest. No protest accompanied the payment of additional search fees.

Form PCT/ISA/210 (continuation of first sheet(1))(July 1992)*